

# Material Safety Data Sheet

Date of Preparation: Jan 09, 08

2 pages

## Section 1 – Chemical Product and Company Identification

Product Name: 100V ESTER OIL WITH UV DYE Part Number(s): 511102 CAS Number: NOT APPLICABLE TO MIXTURES Product Class: Automotive product

Manufacturer: Cliplight Mfg Co., 961 Alness Street, Toronto ON, Canada M3J 2J1 Information Phone No.: 1-800-526-7096 Emergency Phone No.: 1-800-526-7096

Ingredient Name	CAS Number	OSHA TWA	ACGIH TLV
Polyol Esters	Proprietary	-	-
UV Dye	Proprietary	10ppm	10ppm
Proprietary Ingredients			

### Section 3 – Physical and Chemical Properties

Physical State: Liquid Appearance/Odor: Yellow/Bland Odor % Volatile: N/A Evaporation Rate: N/A Boiling Range: Not determined Vapor Density (Air=1) Heavier than air Specific Gravity (@C20 °C): 0.977 Vapor Pressure: 0.1 mm/Hg @ 20C

## **Section 4 – Fire Fighting Measures**

Flash Point: 260C Flash Point Method: Open Cup LEL: N/A Extinguishing Media: Carbon Dioxide, dry chemical, or foam Unusual Fire or Explosion Hazards: Low fire hazard. Unlikely to ignite except in high heat flux conditions. Thermal decomposition will evolve irritant vapors. Special Fire-Fighting Procedures: Use self-contained breathing apparatus with full face piece and protective clothing.

## Section 5 – Stability and Reactivity

Stability: Stable Polymerization: Will not occur Incompatibilities & Conditions to Avoid: Strong Oxidizing Agents Hazardous Decomposition Products: Highly unlikely under intended handling and use.

### Section 6 – Health Hazard Information

Primary Entry Routes: Skin, dermal, inhalation and ingestion Target Organs: Eyes, skin, respiratory system Effects of Overexposure: Prolonged and repeated contact can cause skin irritation. High concentrations of aerosols or mists may be slightly irritating to the upper respiratory tract.

Carcinogenicity: No components of the product are a carcinogen. Chronic Effects: N/A

**Emergency and First Aid Procedures** 

Inhalation: Remove to fresh air. If a cough or other respiratory symptoms develop, consult medical personnel.

Eye Contact: Irrigate with eyewash solution or clean water, holding eyelids apart, for at least 10 minutes. If redness, itching or a burning sensation develops, have eyes examined and treated by medical personnel.

Skin Contact: Remove contaminated clothing. Wash material off of the skin with plenty of soap and water. If redness, itching, or a burning sensation develops, get medical attention. Wash contaminated clothing and decontaminate footwear before reuse.

Ingestion: Do NOT induce vomiting. Wash out mouth with water and give 1 or 2 glasses of water to drink. If gastrointestinal symptoms develop, consult medical personnel. (Never give anything by mouth to an unconscious person).

## Section 7 – Spill, Leak, and Disposal Procedures

Wear skin protection during clean-up. Contain and absorb large spillages onto an inert, nonflammable absorbent carrier (such as earth or sand). Do not allow to enter drains, sewers or waterways. Shovel into a chemical waste container for disposal or recovery.

#### Section 8 – Exposure Controls / Personal Protection

Ventilation: No OSHA PELS or ACGIH TLVs have been assigned. Minimize exposure in accordance with good industrial hygiene practice.

Protective Clothing/Equipment: Wear ISGA standard goggles or face shield. Wear gloves, apron & footwear impervious to this material. Wash clothing before reuse.

Safety Stations: Provide eyewash station and safety shower in work area. Use ventilation adequate to maintain safe levels.

